

Material Safety Data Sheet



Date of issue 1 January 2015

Version 12

1. Product and company identification

Product name : HS ALKYD PRIMER WHITE
Code : QAP135-WHT
Supplier : PPG Industries, Inc.
One PPG Place
Pittsburgh, PA 15272
Emergency telephone number : (412) 434-4515 (U.S.)
(514) 645-1320 (Canada)
01-800-00-21-400 (Mexico)
Technical Phone Number : (905) 823-1100 (MISSISSAUGA ,ONTARIO, CANADA) 8:00 a.m. - 4:30 p.m. Eastern

2. Hazards identification

Emergency overview : DANGER!
FLAMMABLE LIQUID AND VAPOR. CAUSES RESPIRATORY TRACT IRRITATION. MAY BE HARMFUL IF INHALED OR SWALLOWED. SANDING AND GRINDING DUSTS MAY BE HARMFUL IF INHALED. MAY CAUSE EYE IRRITATION. PROLONGED OR REPEATED CONTACT MAY DRY SKIN AND CAUSE IRRITATION. CONTAINS MATERIAL THAT CAN CAUSE TARGET ORGAN DAMAGE. CANCER HAZARD - CONTAINS MATERIAL WHICH CAN CAUSE CANCER. May form explosive peroxides. Risk of explosion by shock, friction, fire or other sources of ignition. This material increases the risk of fire and may aid combustion. Keep away from heat, sparks and flame. Keep away from flames, such as a pilot light, and any object that sparks, such as an electric motor. Keep away from heat. Do not smoke. Keep away from combustible material. Do not breathe vapor or mist. Do not swallow. Avoid contact with eyes, skin and clothing. Use only with adequate ventilation. Keep container tightly closed and sealed until ready for use. Wash thoroughly after handling.

Potential acute health effects

Inhalation : May be harmful if inhaled. Severely irritating to the respiratory system. Can irritate eyes, nose, mouth and throat.
Ingestion : May be harmful if swallowed.
Skin : May cause skin dryness and irritation.
Eyes : Moderately irritating to eyes.

Over-exposure signs/symptoms

Repeated exposure to high vapor concentrations may cause irritation of the respiratory system and permanent brain and nervous system damage. Inhalation of vapor/aerosol concentrations above the recommended exposure limits causes headaches, drowsiness and nausea and may lead to unconsciousness or death. There is some evidence that repeated exposure to organic solvent vapors in combination with constant loud noise can cause greater hearing loss than expected from exposure to noise alone. This product contains crystalline silica which can cause lung cancer or silicosis. The risk of cancer depends on the duration and level of exposure to dust from sanding surfaces or mist from spray applications.

Medical conditions aggravated by over-exposure : Pre-existing disorders involving any target organs mentioned in this MSDS as being at risk may be aggravated by over-exposure to this product.

This Material Safety Data Sheet has been prepared in accordance with Canada's Workplace Hazardous Materials Information System (WHMIS) and the OSHA Hazard Communication Standard (29 CFR 1910.1200).

See toxicological information (Section 11)

3 . Composition/information on ingredients

<u>Name</u>	<u>CAS number</u>	<u>%</u>
☑ Limestone	1317-65-3	10 - 30
n-butyl acetate	123-86-4	10 - 30
titanium dioxide	13463-67-7	7 - 13
Talc , not containing asbestiform fibres	14807-96-6	5 - 10
pentan-2-one	107-87-9	3 - 7
ethyl 3-ethoxypropionate	763-69-9	1 - 5
toluene	108-88-3	0.1 - 1
xylene	1330-20-7	0.1 - 1
crystalline silica, respirable powder (<10 microns)	14808-60-7	0.1 - 1

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

4 . First aid measures

If ingestion, irritation, any type of overexposure or symptoms of overexposure occur during or persists after use of this product, contact a POISON CONTROL CENTER, EMERGENCY ROOM OR PHYSICIAN immediately; have Material Safety Data Sheet information available. Never give anything by mouth to an unconscious or convulsing person.

- Eye contact** : Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Seek immediate medical attention.
- Skin contact** : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.
- Inhalation** : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
- Ingestion** : If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do NOT induce vomiting.
- Notes to physician** : No specific treatment. Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

5 . Fire-fighting measures

Flammability of the product : Flammable liquid. Risk of explosion by shock, friction, fire or other sources of ignition. May form explosive peroxide. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Vapors may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back. Runoff to sewer may create fire or explosion hazard. Avoid shock and friction. Keep away from heat, sparks and flame.

Extinguishing media

Suitable : Use dry chemical, CO₂, water spray (fog) or foam.

Not suitable : Do not use water jet.

Special exposure hazards : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Hazardous combustion products : Decomposition products may include the following materials:
carbon oxides
phosphorus oxides
metal oxide/oxides

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

6 . Accidental release measures

- Personal precautions** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see Section 8).
- Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
- Large spill** : Stop leak if without risk. Move containers from spill area. Approach release from upwind. Use spark-proof tools and explosion-proof equipment. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Do not absorb in sawdust or other combustible material. It may lead to a fire risk when it dries out. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.
- Small spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble or absorb with an inert dry material and place in an appropriate waste disposal container. Do not absorb in sawdust or other combustible material. It may lead to a fire risk when it dries out. Dispose of via a licensed waste disposal contractor.

7 . Handling and storage

- Handling** : Materials such as cleaning rags, paper wipes and protective clothing, which are contaminated with the product may spontaneously self-ignite. To avoid the risks of fires, all contaminated materials should be placed in a metal container filled with water and sealed. Contaminated materials should be removed from the workplace at the end of each working day and be stored outside. Put on appropriate personal protective equipment (see Section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Do not breathe vapor or mist. Do not swallow. Do not get in eyes or on skin or clothing. Avoid shock and friction. Avoid all possible sources of ignition (spark or flame). Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use non-sparking tools. Take precautionary measures against electrostatic discharges. Vapors are heavier than air and may spread along floors. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. Keep away from combustible material. Empty containers retain product residue and can be hazardous. Do not reuse container. If this material is part of a multiple component system, read the Material Safety Data Sheet(s) for the other component or components before blending as the resulting mixture may have the hazards of all of its parts.
- Storage** : Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Eliminate all ignition sources. Separate from oxidizing materials. Separate from reducing agents and combustible materials. See NFPA 430, Code for the Storage of Liquid and Solid Oxidizers. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. Do not store above the following temperature: 120F / 49C.

8 . Exposure controls/personal protection

Name	Result	ACGIH	OSHA	Ontario	Mexico	PPG
Limestone	TWA	Not established	15 mg/m ³ TD	Not established	10 mg/m ³	Not established
	STEL	Not established	5 mg/m ³ R Not established	Not established	20 mg/m ³	Not established
n-butyl acetate	TWA	150 ppm	150 ppm	150 ppm	150 ppm	Not established
	STEL	200 ppm	Not established	200 ppm	200 ppm	Not established
titanium dioxide	TWA	10 mg/m ³	15 mg/m ³ TD	10 mg/m ³ TD	10 mg/m ³ (as Ti)	Not established
	STEL	Not established	Not established	Not established	20 mg/m ³ (as Ti)	Not established
Talc , not containing asbestiform fibres	TWA	2 mg/m ³ R	20 mppcf Z	2 mg/m ³ R	2 mg/m ³ R	Not established
				2 mg/m ³ R	6 mg/m ³ 3 mg/m ³ R	
pentan-2-one	TWA	Not established	200 ppm	Not established	200 ppm	Not established
	STEL	150 ppm	Not established	150 ppm	Not established	Not established
ethyl 3-ethoxypropionate	TWA	Not established	Not established	50 ppm	Not established	50 ppm
	STEL	Not established	Not established	Not established	Not established	100 ppm
toluene	TWA	20 ppm	200 ppm Z	20 ppm	50 ppm S	Not established
	STEL	Not established	500 ppm Z A 300 ppm Z C	Not established	Not established	Not established
xylene	TWA	100 ppm	100 ppm	100 ppm	100 ppm	Not established
	STEL	150 ppm	Not established	150 ppm	150 ppm	Not established
crystalline silica, respirable powder (<10 microns)	TWA	0.025 mg/m ³ R	10 MG/M3 / (%SiO ₂ +2) R Z 250 MPPCF / (%SiO ₂ +5) R Z	0.1 mg/m ³ R	0.1 mg/m ³ R	Not established

Key to abbreviations

A = Acceptable Maximum Peak
 ACGIH = American Conference of Governmental Industrial Hygienists.
 C = Ceiling Limit
 F = Fume
 IPEL = Internal Permissible Exposure Limit
 OSHA = Occupational Safety and Health Administration.
 R = Respirable

S = Potential skin absorption
 SR = Respiratory sensitization
 SS = Skin sensitization
 STEL = Short term Exposure limit values
 TD = Total dust
 TLV = Threshold Limit Value
 TWA = Time Weighted Average

8 . Exposure controls/personal protection

Z = OSHA 29CFR 1910.1200 Subpart Z - Toxic and Hazardous Substances

Consult local authorities for acceptable exposure limits.

Recommended monitoring procedures : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

Engineering measures : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Personal protection

Eyes : Safety glasses with side shields.

Hands : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Respiratory : If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Skin : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.

Environmental exposure controls : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

9 . Physical and chemical properties

Physical state	: Liquid.
Flash point	: Open cup: 20°C (68°F)
Explosion limits	: Lower: 1.3%
Color	: Not available.
Odor	: Not available.
pH	: Not available.
Boiling/condensation point	: 38°C (100.4°F)
Melting/freezing point	: Not available.
Specific gravity	: 1.42
Density (lbs / gal)	: 11.85

9 . Physical and chemical properties

Vapor pressure	: 2 kPa (15.2 mm Hg) [room temperature]
Vapor density	: Not available.
Volatility	: 43% (v/v), 25.95% (w/w)
Evaporation rate	: 1.22 (butyl acetate = 1)
Solubility	: Insoluble in the following materials: cold water.
Partition coefficient: n-octanol/water	: Not available.
% Solid. (w/w)	: 74.05

10 . Stability and reactivity

Stability	: Stable under recommended storage and handling conditions (see Section 7).
Conditions to avoid	: Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition. Drying on clothing or other combustible materials may cause fire.
Materials to avoid	: Reactive or incompatible with the following materials: combustible materials, organic materials, metals, acids, alkalis, oxidizing materials, reducing materials
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.
Hazardous polymerization	: Under normal conditions of storage and use, hazardous polymerization will not occur.

11 . Toxicological information

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
n-butyl acetate	LD50 Oral	Rat	10.768 g/kg	-
	LD50 Dermal	Rabbit	>17600 mg/kg	-
	LC50 Inhalation	Rat	>21.1 mg/l	4 hours
titanium dioxide	LD50 Oral	Rat	>10 g/kg	-
	LD50 Dermal	Rabbit	6500 mg/kg	-
pentan-2-one	LD50 Oral	Rat	1600 mg/kg	-
	LD50 Dermal	Rabbit	3200 mg/kg	-
ethyl 3-ethoxypropionate	LD50 Oral	Rabbit	10 mL/kg	-
	LD50 Dermal	Rabbit	636 mg/kg	-
toluene	LD50 Oral	Rat	8.39 g/kg	-
	LD50 Dermal	Rabbit	49 g/m3	4 hours
xylene	LC50 Inhalation	Rat	4.3 g/kg	-
	LD50 Oral	Rat	>1.7 g/kg	-
	LD50 Dermal	Rabbit	>1.7 g/kg	-
	LC50 Inhalation	Rat	5000 ppm	4 hours
	Vapor			

Conclusion/Summary : Not available.

Chronic toxicity

Conclusion/Summary : Not available.

Defatting irritant

: Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis.

Target organs

: Contains material which causes damage to the following organs: brain.
Contains material which may cause damage to the following organs: lungs, cardiovascular system, upper respiratory tract, skin, central nervous system (CNS), eye, lens or cornea.

Carcinogenicity

11 . Toxicological information

Carcinogenicity : Contains material which can cause cancer. Risk of cancer depends on duration and level of exposure.

Classification

Product/ingredient name	ACGIH	IARC	NTP
Titanium dioxide	A4	2B	-
toluene	A4	3	-
crystalline silica, respirable powder (<10 microns)	A2	1	Known to be a human carcinogen.

Carcinogen Classification code:
 ACGIH: A1, A2, A3, A4, A5
 IARC: 1, 2A, 2B, 3, 4
 NTP: Proven, Possible
 Not listed or regulated as a carcinogen: -

Developmental effects : Contains material which may cause developmental abnormalities, based on animal data.

Fertility effects : Contains material which may impair female fertility, based on animal data.

12 . Ecological information

Environmental effects : No known significant effects or critical hazards.

Aquatic ecotoxicity

Product/ingredient name	Result	Species	Exposure
Titanium dioxide	Acute LC50 >100 mg/l Fresh water	Daphnia - Daphnia magna	48 hours

13 . Disposal considerations

Waste disposal : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees. Section 6. Accidental release measures

14. Transport information

14. Transport information

	DOT	TDG	Mexico	IMDG
UN number	UN1263	UN1263	UN1263	UN1263
UN proper shipping name	PAINT RELATED MATERIAL	PAINT RELATED MATERIAL	PAINT RELATED MATERIAL	PAINT RELATED MATERIAL
Transport hazard class(es)	3	3	3	3
Packing group	II	II	II	II
Environmental hazards	No.	No.	No.	No.
Marine pollutant substances	Not applicable.	Not applicable.	Not applicable.	Not applicable.
Product RQ (lbs)	30466.7	Not applicable.	Not applicable.	Not applicable.
RQ substances	(n-butyl acetate, xylene)	Not applicable.	Not applicable.	Not applicable.

Additional information

DOT : Package sizes shipped in quantities less than the product reportable quantity are not subject to the RQ (reportable quantity) transportation requirements.

TDG : None identified.

Mexico : None identified.

IMDG : None identified.

Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

15. Regulatory information

United States inventory (TSCA 8b) : All components are listed or exempted.

Australia inventory (AICS) : At least one component is not listed.

Canada inventory (DSL) : All components are listed or exempted.

China inventory (IECSC) : At least one component is not listed.

Europe inventory (REACH) : Please contact your supplier for information on the inventory status of this material.

Japan inventory (ENCS) : At least one component is not listed.

Korea inventory (KECI) : At least one component is not listed.

New Zealand (NZIoC) : Not determined.

Philippines inventory (PICCS) : At least one component is not listed.

United States

U.S. Federal regulations :

SARA 302/304: No products were found.

SARA 311/312 SDS Distribution - Chemical Inventory - Hazard Identification:

Chemical name **CAS #** **Acute** **Chronic** **Fire** **Reactive** **Pressure**

Product code QAP135-WHT

Date of issue 1 January 2015

Version 12

Product name HS ALKYD PRIMER WHITE

15. Regulatory information

<input checked="" type="checkbox"/> Limestone	1317-65-3	N	N	N	N	N
n-butyl acetate	123-86-4	Y	N	Y	N	N
titanium dioxide	13463-67-7	N	Y	N	N	N
Talc , not containing asbestiform fibres	14807-96-6	Y	N	N	N	N
pentan-2-one	107-87-9	Y	N	Y	N	N
ethyl 3-ethoxypropionate	763-69-9	Y	N	Y	Y	N
toluene	108-88-3	Y	Y	Y	N	N
crystalline silica, respirable powder (<10 microns)	14808-60-7	N	Y	N	N	N
Product as-supplied :		Y	Y	Y	Y	N

SARA 313

Supplier notification

Chemical name

: zinc bis(orthophosphate)

CAS number

7779-90-0

Concentration

1 - 5

Additional environmental information is contained on the Environmental Data Sheet for this product, which can be obtained from your PPG representative.

California Prop. 65

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

Canada

WHMIS (Canada)

: Class B-2: Flammable liquid with a flash point lower than 37.8°C (100°F). Class D-2A: Material causing other toxic effects (Very toxic). Class D-2B: Material causing other toxic effects (Toxic).

Mexico

Classification

Flammability : 3 Health : 2 Reactivity : 0

16. Other information

Hazardous Material Information System (U.S.A.)

Health : 2 * Flammability : 3 Physical hazards : 0

(*) - Chronic effects

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

The customer is responsible for determining the PPE code for this material.

National Fire Protection Association (U.S.A.)

Health : 2 Flammability : 3 Instability : 0

Date of previous issue : 8/26/2014.

Organization that prepared the MSDS : EHS

Indicates information that has changed from previously issued version.

Disclaimer

16 . Other information

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.