



# Waterborne Acrylic Sanding Primer



## An exceptional sanding primer for interior wood

AQUACRON® 270 Series waterborne acrylic sanding primer and sealer is a single-component product designed for use with interior wood and wood related products. With excellent sanding properties, this primer also has a very fast dry time.

### The PPG Benefit

- Good hardness and adhesion
- Ready to spray
- Excellent sanding properties
- Very fast dry time
- Water reduction and cleanup
- 1.0 lbs./gal. VOC (120 g/L)

### Segments

- Interior doors
- Interior windows and trim
- Interior shutters
- Interior cabinetry and furniture
- Interior signage and displays





Paired with more than 1,000 professional service centers across North America and an industry-leading technical team, the PPG TRUEFINISH® team provides a vast lineup and knowledge of high-quality industrial coatings backed by local store stocking and delivery. This system ensures you get the products and knowledge you need when you need them.

**Product Characteristics**

Color	White
Gloss @ 60° (ASTM D523)	0 - 5
VOC	1.0 lbs./gal. (120 g/L)
Dry Time	
To Touch	10 - 20 minutes
To Handle	20 - 40 minutes
To Topcoat / Recoat	1 - 2 hours
To Sand	30 minutes
Applications	Interior wood, plastics

**Performance Properties**

Adhesion (ASTM D3359)	5B - Excellent
-----------------------	----------------



This document contains general information only and should not be construed as creating any warranties, express or implied. Please contact a PPG representative for additional information. *Aquacron*, the *PPG Logo* and *PPG TrueFinish* are registered trademarks and *We protect and beautify the world* is a trademark of PPG Industries Ohio, Inc. The *Twitter Logo* is a registered trademark of Twitter, Inc. The *IN Logo* is a registered trademark of LinkedIn Corporation. ©2019 PPG Industries, Inc. All rights reserved. 06/19 TF2048

